

Resilient Flooring — Organic Collection

Bio-based resilient flooring · Uniclass Ss_25_30_70

Editable NBS-format clause for specification (NBS Chorus / legacy M50). Product-specific values are shown in [square brackets] — request the current Technical Data Sheet and the EN 13501-1 classification report for exact figures.

M50 / 120 RESILIENT FLOORING

- **Manufacturer / supplier:** The Floor Gallery — www.thefloorgallery.co.uk.
- **Product reference:** Organic flooring, decor [decor name]; format [tile & plank / sheet].
- **Composition:** PVC-free, bio-based resilient flooring (castor / canola oil, chalk); carbon-neutral; zero VOC.
- **Use class:** To BS EN ISO 10874 — Class 43 (heavy commercial) [confirm].
- **Reaction to fire:** BS EN 13501-1 — class [confirm classification report].
- **Slip resistance:** [confirm PTV / R-value as required].
- **Environmental:** PVC-free; carbon-neutral; EPD available on request.

M50 / 220 & 320 SUBSTRATE & INSTALLATION

- Subfloor flat (SR1), sound, clean, dry; max 75% RH (BS 8203) or surface DPM.
- Fully bonded with manufacturer-approved adhesive; or click-system floating per product.
- Seal / finish coats: [as supplied / site-applied — confirm].

Uniclass 2015: Ss_25_30_70 — Resilient floor finish systems.