



SilentLay3.0

*High-performance acoustic cork & rubber underlay
for resilient flooring systems*



SilentLay3.0 3mm is designed to be used as an underlay, underscreed and overscreed. Ideal to be used to reduce sound transmission on various floor finishes. Produced with recycled car tyres and cork.

PRODUCT SPECIFICATION

CHARACTERISTICS	TYPICAL RESULT
Composition	Cork and recycled car tyres
Roll Length	15m
Roll Width	1m
Weight	2.19kg/m ²
Total m ²	15m ²
Thickness	3mm
Density	730kg/m ³
Tensile Strength	>770KPa
Compression	16%
Recovery from Compression	>75%
Tog Rating	0.33



RECYCLED CAR TYRES



NATURAL CORK



IMPACT NOISE REDUCTION



PERFORMANCE DATA

Acoustic Performance

FLOOR FINISH	DB RESULT
Concrete subfloor stand alone	18dB

Recommended Adhesives

FLOOR FINISH	ADHESIVE
LVT	Mapei VS90 Plus, Uzin KE66
Carpet Tiles	Ultrabond Eco Tack, F.Ball F41
Vinyl	Mapei VS90 Plus, F.Ball F44
Linoleum	Mapei ECO 520
Engineered Wood	MonoSil P
Cork (click)	MonoSil P



“Beautiful Floors, Better Future”

SilentLay3.0 combines the natural acoustic comfort of cork with the resilience of recycled rubber — a sustainable underlay engineered to quieten every step, across both domestic and commercial applications.

✉ aaron.smith@thefloorgallery.co.uk

🌐 thefloorgallery.co.uk